



Reed Schalter

	DRR-129 Standard	A standard, normally open switch with a 50.80mm long x 5.25mm diameter (2.000" x .207") glass envelope, capable of high voltage and power switching up to 400Vdc at 100W.
	DRR-DTH Standard Changeover	A standard changeover switch with a 39.67mm long x 5.33mm diameter (1.562" x 0.210") glass envelope, capable of high voltage and power switching up to 500Vdc at 30W.
	DRT-DTH Standard Changeover	A standard changeover switch with a 39.67mm long x 5.33mm diameter (1.562" x 0.210") glass envelope, with tungsten contacts capable of high voltage and power switching up to 500Vdc at 50W.
	FLEX-14 Sub-miniature	A sub-miniature, normally open switch with a 14.00mm long x 2.28mm diameter (0.551" x 0.090") glass envelope and longer than standard, flexible easily formed leads, capable of switching 200Vdc at 10W.
	MARR-5 Miniature HV	A miniature, normally open switch with a 19.69mm long x 2.66mm diameter (0.775" x 0.105") glass envelope, capable of high voltage switching of up to 1kVdc at 1mA.
	MDCG-4 Sub-miniature	A sub-miniature, normally open switch with a 15.24mm long x 2.28mm diameter (0.600" x 0.090") glass envelope, capable of switching 200Vdc at 10W.
	MDRR-6 Sub-miniature HV	A sub-miniature, normally open switch with a 15.24mm long x 2.28mm diameter (0.600" x 0.090") glass envelope, capable of high voltage switching of 265Vac at 10VA.








Zur Beachtung: Es handelt sich um Illustrationen nicht um Datenblätter. Wir bitten diese gesondert anzufordern.

Reed Schalter

	MDRR-DT Miniature Changeover	A miniature changeover switch with a 14.73mm long x 2.54mm diameter (0.580" x 0.100") glass envelope, capable of switching 175Vdc at 5W. Sensitivity range 15-30 AT.
	MDSM-10 Sub-miniature Surface Mount	A sub-miniature, surface mounting, normally open switch with a 10.16mm long x 1.80mm diameter (0.400" x 0.071") glass envelope. UL recognised and capable of switching 200Vdc at 10W.
	MDSM-4 Sub-miniature Surface Mount	A sub-miniature, surface mounting, normally open switch with a 15.24mm long x 2.28mm diameter (0.600" x 0.090") glass envelope. UL recognised and capable of switching 200Vdc at 10W.
	MDSM-DT Miniature Changeover Surface Mount	A miniature, surface mounting, changeover switch with a 14.73mm long x 2.54mm diameter (0.580" x 0.100") glass envelope. UL recognised and capable of switching 175Vdc at 5W.
	MDSR-10 Sub-miniature	A sub-miniature, normally open switch with a 10.16mm long x 1.80mm diameter (0.400" x 0.071") glass envelope, capable of switching 200Vdc at 10W.
	MDSR-7 Sub-miniature	A sub-miniature, normally open switch with a 12.70mm long x 1.80mm diameter (0.500" x 0.071") glass envelope, capable of switching 200Vdc at 10W.
	MISM-3V1 Ultra-miniature Surface Mount	An ultra-miniature, surface mounting, normally open switch with a 7.00mm long x 1.80mm diameter (0.276" x 0.071") glass envelope, capable of switching 170Vdc at 10W.

Zur Beachtung: Es handelt sich um Illustrationen nicht um Datenblätter. Wir bitten diese gesondert anzufordern.

Reed Schalter

	MITI-3V1 Ultra-miniature	An ultra-miniature, normally open switch with a 7.00mm long x 1.80mm diameter (0.276" x 0.071") glass envelope.
	MLRR-3 Miniature CD	A miniature, normally open switch with a 15.24mm long x 2.54mm diameter (0.600" x 1.000") glass envelope, capable of switching 200Vdc at 20W with close differential (CD) characteristics.
	MLRR-4 Sub-miniature CD	A sub-miniature, normally open switch with a 15.24mm long x 2.54mm diameter (0.600" x 1.000") glass envelope, capable of switching 200Vdc at 20W with close differential (CD) characteristics.
	MLSM-3 Miniature CD Surface Mount	A miniature, surface mounting, normally open switch with a 15.24mm long x 2.54mm diameter (0.600" x 1.000") glass envelope. UL recognised and capable of switching 200Vdc at 20W with close differential (CD) characteristics.
	MLSM-4 Sub-miniature CD Surface Mount	A sub-miniature, surface mounting, normally open switch with a 15.24mm long x 2.54mm diameter (0.600" x 1.000") glass envelope. UL recognised and capable of switching 200Vdc at 20W with close differential (CD) characteristics.
	MRPR-3 Miniature Power	A miniature, normally open switch with a 19.69mm long x 2.84mm diameter (0.770" x .112") glass envelope, capable of switching up to 200Vdc at 50W.
	MRPR-8 Miniature HV	A miniature, normally open switch with a 20.32mm long x 2.84mm diameter (0.800" x 0.112") glass envelope, capable of high voltage and power switching of 265Vac at 50VA.

Zur Beachtung: Es handelt sich um Illustrationen nicht um Datenblätter. Wir bitten diese gesondert anzufordern.

REHAG ELEKTRONIK – Bereich Industrieelektronik
Tel. 04261 / 9388-120 Fax: 04261 / 9388-920
ottermann@rehag.de www.rehag.de